Commercial Fishing Vessel Safety Exam Checklist

Documented Vessels 65' to < 79', within Coastal Waters

Vessel Name:	Number:		
BRIDGE & DOCUMENTS			
33 CFR 173 46 CFR 67	Registration/Documents/Markings: Certificate of documentation on board & valid. Name on both sides, forward part of hull, name & hailing port on stern, ≥ 4" letters, contrasting color. Official number permanently marked on main beam.	O Yes O No O N/A	
46 CFR 28.165	Injury Placard: Required on all vessels.	O Yes O No O N/A	
33 CFR 155.450	Oil Pollution Placard: Required on all vessels ≥ 26'.	O Yes O No O N/A	
33 CFR 151.59	MARPOL (Garbage) Placard: Required on all vessels ≥ 26'.	O Yes O No O N/A	
33 CFR 151.57	Waste Management Plan: Required on all oceangoing vessels >40'.	O Yes O No O N/A	
33 USC 1602 33 USC 2020 72 COLREGS	Navigation Lights: During darkness and/or in or near areas of restricted visibility Side Lights (112.5°), Mast Head Light (225°) & Stern Light (135°). Fishing Lights: In a vertical line, one meter apart. Red over White (360°) all other than trawling; Green over White (360°) when trawling.	O Yes O No O N/A	
33 USC 1602 33 USC 2020 72 COLREGS	Dayshapes: Two black cones, apex to apex (not required on trollers).	O Yes O No O N/A	
33 USC 1602 33 USC 2020 72 COLREGS	Sound Producing Devices: Vessels 12m – 20m (39.4' – 65.6'): Whistle audible for ½ mile & 7.9" bell. Vessels 20m – 100m (65.6' – 328.1'): Whistle audible for 1 mile & 11.8" bell.	O Yes O No O N/A	
46 CFR 28.210	First Aid/CPR: If operating beyond the Boundary Line, requires first aid & CPR trained & certified persons on board (POB) as follows: > 3 POB, one each; >17 POB, two each; one POB holding both certifications is acceptable. Requires "suitable" first aid kit & first aid manual.	O Yes O No O N/A	
46 CFR 28.225	Navigation Publications: If operating beyond the Boundary Line, requires corrected marine charts of operating area, U. S. Coast Pilot, Coast Guard Light List, Tide & Tidal Current Tables & a copy of Inland Navigation Rules.	O Yes O No O N/A	
46 CFR 28.230	Magnetic Compass/Compass Deviation Table: If operating beyond the Boundary Line, requires operable magnetic compass at operating station & a current compass deviation table.	O Yes O No O N/A	
46 CFR 28.245 47 CFR 80 33 CFR 26.03 46 CFR 28.375	Communication Equipment: Requires a VHF-FM radiotelephone (156 – 162 MHz) at the operating station, capable of operating three hours off an emergency power supply.	O Yes O No O N/A	
47 CFR 80.405	FCC Ship Radio Station License: Documented vessels required to carry radio transmitting equipment are required to have on board a current FCC Ship Radio Station License.	O Yes O No O N/A	
46 CFR 28.240	General Alarm System: If operating beyond the Boundary Line & if there is an accommodation or workspace not adjacent to the operating station, requires an audible general alarm system with contact maker at the operating station; flashing red light in workspaces where the audible alarm is hard to hear (engine room), & red-letter warning signs "Attention General Alarm – When Alarm Sounds, Go To Your Station" at each bell or light. Public address system may be used if it meets criteria. Test prior to operating vessel & weekly afterwards.	O Yes O No O N/A	
46 CFR 28.250	High Water Alarms: If operating beyond the Boundary Line, requires a visible & audible alarm at operating station to indicate high water in normally unmanned or non-watertight spaces (engine room, lazarette, fish hold, etc.).	O Yes O No O N/A	
46 CFR 28.265	Emergency Instructions: If operating beyond the Boundary Line, requires written	O Yes O No O N/A	
46 CFR 28.270	Emergency Instructions. Must be posted if \geq 4 POB, kept available if \leq 4 POB. Instructions, Drills, & Safety Orientation: If operating beyond the Boundary Line, requires master or individual-in-charge ensure monthly drills & instructions given to each person on board by a trained drill conductor. There are ten Required Drills & Instructions. Before operating vessel, persons on board who have not had drills & instruction must receive a safety orientation.	O Yes O No O N/A	

Commercial Fishing Vessel Safety Exam Checklist Documented Vessels 65' to < 79', within Coastal Waters

46 CFR 28.235	Anchors & Radar Reflectors: If operating beyond the Boundary Line, requires radar reflector if vessels lacks strong radar signature (usually fiberglass hull vessels). Requires adequate anchor & sufficient line/cable for operating area.	O Yes O No O N/A
<i>LIFESAVING</i>		
46 CFR 28.145 46 CFR 28.140	Visual Distress Signals: 3 hand-held rocket-propelled parachute red flares plus 6 hand red flares plus 3 floating orange smoke distress signals.	O Yes O No O N/A
46 CFR 28.110 46 CFR 28.135 46 CFR 28.140	Personal Flotation Devices (PFDs): Inside the Boundary Line, requires one Type I, V or immersion suit for each person on board. If operating beyond the Boundary Line, requires one immersion suit for each person on board. Immersion suit needs PFD light, PFD marked w/name of vessel/wearer & retroreflective tape (31 sq. in.) front & back, properly maintained & stowed readily accessible.	O Yes O No O N/A
46 CFR 28.115 46 CFR 28.135	Ring Life Buoys: Three 24" ring life buoys, one w/90" of floating line, marked w/vessel name/number, 4 strips of retroreflective tape & stowed readily accessible.	O Yes O No O N/A
46 CFR 28.120 46 CFR 28.125 46 CFR 28.130 46 CFR 28.140	Survival Craft: Inside Boundary Line; none required for warm water operations; for cold water operations, buoyant apparatus required if < 4 persons on board & inflatable buoyant apparatus required if ≥ 4 persons on board. From the Boundary Line out to three miles: For both cold & warm water operations; if < 4 persons on board requires a buoyant apparatus. If ≥ 4 persons on board; warm water operations requires a life float; cold water operations require an inflatable buoyant apparatus. Life float & buoyant apparatus must be marked w/vessel name/number, four strips retroreflective tape, 100' painter & electric light; stowed to float free. Inflatable buoyant apparatus may be stowed to float free or kept readily available.	O Yes O No O N/A
ENGINE ROOM/MISCELLANEOUS		
46 CFR 28.155 46 CFR 28.160 46 CFR 25.30	Portable Fire Extinguishing Equipment: Two C-I in pilothouse, one B-II or C-II in galley, two B-II in engine room & one B-II outside auxiliary spaces. Must be USCG, UL or FM approved; mounted in approved bracket; in good condition; must have pressure gauge or inspection record.	O Yes O No O N/A
33 CFR 159.7	Marine Sanitation Device: Type II or III; required only if there is an installed toilet on board; Type III must be fitted with a positive means (padlock/wire tie) of securing overboard discharge valve when vessel is not > 3 miles from shore.	O Yes O No O N/A
46 CFR 28.215	Guards for Exposed Hazards: If operating beyond the Boundary Line, requires suitable hand covers, guards, or railings in way of machinery (gearing, chain or belt drives, rotating shafts, etc.) that may injure personnel. Not to restrict access to fishing gear.	O Yes O No O N/A
46 CFR 28.255	Bilge Pump, Piping & Dewatering Systems: If operating beyond the Boundary Line, requires bilge pumps & piping capable of dewatering any watertight space.	O Yes O No O N/A
50 CFR 600.730	Safe Boarding Ladder: Vessels with more than 4' of freeboard.	O Yes O No O N/A

IF VESSEL IS GREATER THAN 100 GT, USE SUPPLEMENT 1 (CG-5587b)

To schedule a "no fault, no penalty" voluntary dockside examination, please contact one of these fishing vessel safety professionals:

In Maryland, call:

In Virginia, call:

In southern New Jersey, call:

In North Carolina, call

the Baltimore, MD Examiner at (410) 576-2634 the Norfolk, VA Examiner at (757) 668-5533 the Philadelphia, PA Examiner at (215) 271-4989

the Atlantic Beach, NC Examiner at (252) 247-4562